

# Portable Meters

## MULTIMETERS



MI 7065

Due to electric and constructional features the analogue and digital universal meters are intended for a wide range of users. They are especially convenient for repair shops, electric, radio and electronic professions as well as for the field work. Ratings are protected against overloads when the meters are connected to 250 V.

TYPE		MI 7054	MI 7056	MI 7065
Voltage	=	30 V ... 600 V	100 mV ... 600 V	100 mV-300 V
	~	30 V ... 600 V	10 V ... 600 V	3 V-300 V
Current	=	0.3 A ... 15 A	50 $\mu$ A ... 1 A	100 $\mu$ A-3 A
	~	0.3 A ... 15 A	3 mA ... 3 A	100 $\mu$ A-3 A
Characteristic resistance	=	1.45 k $\Omega$ /V	20 k $\Omega$ /V	10 M $\Omega$
	~	1.33 k $\Omega$ /V	6.67 k $\Omega$ /V	10 M $\Omega$
Number of ratings		15	24	25
Resistance	$\Omega$ x	1, 10, 100	1,10,100	-
Level dB		-	•	-
Polarity indication		-	-	-
Accuracy		2.5 $\cong$	2.5 $\cong$	3 $\infty$
				2 $\cong$
Special features		Full protection	-	Zero in the middle of the scale
Supply		1 x 1.5 V R6	1 x 1.5 V R6	1 x 9 V 6F22
Dimensions (mm)		102 x 142 x 40	102 x 142 x 40	96 x 132 x 33
Weight with packing		470 g	340 g	400 g